

## S-50 Single Channel Perimeter Security

FOTAS S-50 is a fiber optic distributed acoustic sensing system that can be used easily in different situations. S-50 keeps your fences and borders safe and sends early warnings of threats. It is one of the proven early systems for security. FOTAS detects third-party intervention, illegal crossing attempts, and unauthorized excavations along a line spanning several kilometers.



## S-50 Technical Details

<b>Fiber Optic Cable</b>	Single-mode fiber optic cable
<b>Detection Channels</b>	Single fiber channel of real time independent intrusion detection
<b>Detection Distance</b>	50 km
<b>Sensing Technology</b>	Coherent Optical Time Domain Reflectometer (COTDR)
<b>Maximum Fiber Loss</b>	10dB (typical max distance ~ 50km /ch)
<b>Operating Life</b>	> 10 years (dependent on operating environment and regular maintenance)
<b>Artificial Intelligence</b>	Deep-learning-based intrusion detection algorithms optimize sensitivity and probability of detection. Locations can be changed with parameters to avoid nuisance alarms. Different algorithms exist for buried and fence applications. The system is hybrid since both are applicable.
<b>Detection Resolution</b>	10 m (32.8 ft) between detection points along sensing fiber (100 measurements per km of sensing fiber) 100 m (328 ft) minimum cable separation between individually reported disturbances (simultaneous)
<b>System Interface</b>	Web 2.0
<b>Sensor Sections</b>	Software configurable, independent sensor sections (detection zones)
<b>Temperature Range</b>	Sensing Cable: -40~70 °C / S-50 Device: 0~40 °C (AC environment)
<b>Connection Ports</b>	TCP/IP (Ethernet), relay closures (via FOTAS connected PLC or ADAM module or alternatives)
<b>Inputs and Outputs</b>	FC/APC single mode optical connector (back, for sensing cable) 1 x USB2 ports (on back) 1 x Ethernet ports (10/100/1000 Mbps, on back)
<b>Power Supply</b>	110 to 240 Vac, 47 to 63 Hz, auto ranging.
<b>Power Consumption</b>	85 W typical, 125 W max
<b>Dimensions / Rack -Clearance / Weight</b>	49 cm (19") x 50 cm x 8.9 cm(2U), 8 kg
<b>Laser Safety Class</b>	Class 1 (IEC 60825-1, 21CFR1040.10), shutoff: key switch on front panel
<b>MTBF</b>	> 80,000 hours
<b>Warranty</b>	2 years, with optional per year warranty extension available.
<b>Regulatory Certification</b>	ISO9001 accredited design and manufacturing is CE certified (Electromagnetic compatibility Directive (EMC) 2014/30/EU (EN 55032:2015 Class A, EN IEC 61000-3-2:2019+A1:2019, EN 61000-3-3:2013+A1:2019, EN 55035:2017+A1:2020, EN 61000-4-2:2009, EN 61000-4-3:2020, EN 61000-4-4:2012, EN 61000-4-5:2014+A1:2017, EN 61000-4-6:2014, EN 61000-4-8:2010, EN 61000-4-11:2020) The low voltage directive (LVD) (2014/35/EU) (IEC 62368-1:2018, EN IEC 62368-1:2020 + A11:2020)

**Contact Details:**

Samm Teknoloji İletişim San. ve Tic. A.Ş.  
 Gebze Organised Industrial Zone (GOSB) Ihsandede Cd. 800. Sok No: 802, 41400 Gebze-Kocaeli, Turkey  
 Telephone: 444 1 726- +90 (262) 677 16 80 | Fax: +90 (262) 677 16 81 | Email: [fotas@samm.com](mailto:fotas@samm.com)



# FOTAS™

## Fiber Optic Distributed Acoustic Sensing System



### Applications

- ✓ *Perimeter Security*
- ✓ *Smart Cities*
- ✓ *Railway Monitoring*
- ✓ *Pipeline Surveillance*
- ✓ *Highway Monitoring*
- ✓ *Infrastructure Monitoring*

